(19) World Intellectual Property Organization International Bureau



) - COLLE DIDITION | COLLEGE C

(43) International Publication Date 28 April 2005 (28.04.2005)

PCT

(10) International Publication Number WO 2005/037637 A1

- (51) International Patent Classification7: B60G 21/00, B62D 9/02
- B62K 5/08,
- (21) International Application Number:

PCT/IB2004/003436

- (22) International Filing Data: 21 October 2004 (21.10.2004)
- (25) Filing Language:

Bnglish

(26) Publication Language:

Bnglish

- (30) Priority Data: 2003/8179
- 21 October 2003 (21.10.2003) ZA
- (71) Applicant and
- (72) Inventor: RAWLINSON, Rodney, lan [ZA/ZA];
 71 Bryanston Crescent, Cnr Hobart & Bantry Roads,
 Bryanston, 2196 SANDTON (ZA).
- (74) Agent: LOOCK, Jacobus, Andries; Adams & Adams, Adams & Adams Place, 1140 Prospect Street, Hatfield, PO Box 1014, 0001 PRETORIA (ZA).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AB, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DB, DK, DM, DZ, EC, EB, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KB, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Burasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Buropean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, BS, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) TILLE: LATERALLY-LEANING FOUR WHEFLED VEHICLE



(57) Abstract: This invention relates to wheeled vehicles and particularly to motorised road vehicles. The wheeled vehicle (10) includes two frames (12) for carrying road wheels (18, 20), the frames (12) being laterally spaced spart. A pair of road wheels (18, 20) are mounted on each frame (12) for supporting that frame (12) on the ground, the wheels (18, 20) of each pair being mounted for rotation about operatively more or less horizontal rotational axes which are spaced apart along the associated frame (12). A motor (36) is connected by a drive train (48, 28, 30, 32) to a rear wheel (20) on each of the wheeled frames (12). The wheeled frames (12) are connected together for synchronous tilting relative to the vertical, so that the camber angles of all the wheels (18, 20) change in response to lateral tilting of the frames (12).

E.9 185.0N

 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

DEST AVAILABLE COPY